



SAFETY DATA SHEET

DATE: 03/09/21

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(a) PRODUCT NAME IDENTIFIER USED ON LABEL:

No. 1 Vary Flex Epoxy Resin, Type HV

(b) OTHER MEANS OF IDENTIFICATION:

Synonyms: Bisphenol A Diglycidel Ether Resin

Chemical formula: $(C_{15}H_{16}O_2-C_3H_5ClO)_x$

CAS Numbers: See section 3

Other: none

(c) RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS

Epoxy resin

(d) NAME, ADDRESS AND TELEPHONE NUMBER OF MANUFACTURER

Manufacturer's Name and Address: IsleChem, LLC

2801 Long Road

Grand Island, NY 14072

Telephone: 716-773-8100

(e) EMERGENCY PHONE NUMBER

24 Hour emergency telephone: 1-800-424-9300

To request an SDS: 1-716-773-8100

Customer service: 1-716-773-8100

2. HAZARDS IDENTIFICATION

(a) CLASSIFICATION OF CHEMICAL IN ACCORDANCE WITH 29 CFR 1910(d)

Health: Eye irritation, category 2A; Skin irritation, category 2; Skin sensitizer, category 1B

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

Physical: none**(b) SYMBOLS, SIGNAL WORD, HAZARD AND PRECAUTIONARY STATEMENTS IN ACCORDANCE WITH 29 CFR 1910.1200(d)****Symbols (Pictograms)****Signal Words, Hazard and Precautionary Statements:**

Warning: Causes serious eye irritation. Causes skin irritation. May cause an allergic skin reaction.

Avoid breathing fumes/mist/vapor/spray. Wear protective gloves. Wash hands thoroughly after handling. Wear eye, and face protection. Take off contaminated clothing and wash it before reuse. Contaminated work clothing must not be allowed out of the workplace.

IF ON SKIN: Wash with plenty of water. If skin irritation occurs, get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists: Get medical attention/advice.

Dispose of contents and container in accordance with local, state and federal regulations.

(c) HAZARDS NOT OTHERWISE CLASSIFIED

None

(d) MIXTURE INGREDIENT(S) THAT ARE NOT CLASSIFIED FOR TOXICITY

None at greater than 1%.

3. COMPOSITION/INFORMATION ON INGREDIENTS

(a) Chemical Name	(b) Common Name & Synonyms	(c) CAS Number	(d) Concentration Weight %
Bisphenol A Diglycidel Ether Resin	none	25068-38-6	92.3%

4. FIRST AID MEASURES

(a) DESCRIPTION OF FIRST AID MEASURES BY ROUTES OF ENTRY

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN: Flush thoroughly with cool water under shower while removing contaminated clothing and shoes. Wash clothing before reuse. GET MEDICAL ATTENTION.

INHALATION: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, have trained person administer oxygen. If respiration stops, have a trained person administer artificial respiration. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. If swallowed, rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. If vomiting occurs spontaneously, keep airway clear and give more water. GET MEDICAL ATTENTION IMMEDIATELY.

(b) MOST IMPORTANT SYMPTOMS AND EFFECTS**Potential health effects:**

Routes of entry: Ingestion, inhalation, skin, eyes.

Target organs: None known.

Irritancy: Irritating to eyes and skin

Sensitizing capability: Skin sensitizer.

Reproductive effects: None known.

Cancer information: This product does not contain any substances at > 0.1 weight % that are considered by OSHA, NTP, IARC or AGCIH to be “probable” or “suspected” carcinogens.

This product contains chemicals known to the State of California to cause cancer.

Short term exposure (acute):

Inhalation: May be harmful if inhaled.

Eyes: Eye irritant

Skin: May cause irritation and sensitization.

Ingestion: May be harmful by ingestion. LD50 > 13g/kg (rat)

Repeated exposure (chronic)

Could cause skin sensitization.

Synergistic materials: None known.

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

Medical conditions aggravated by exposure: None known.

(c) INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

As indicated above

5. FIRE FIGHTING MEASURES

(a) SUITABLE EXTINGUISHING MEDIA

Dry chemical, alcohol foam, carbon dioxide.

(b) SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Not a flammable liquid but will burn under fire conditions. Oxides of carbon form as combustion products.

(c) SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

In fire conditions wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus and full protective clothing. Keep unauthorized personnel removed and upwind.

(note: see section 9 for flash point, LEL, UEL, and auto-ignition temperature)

6. ACCIDENTAL RELEASE MEASURES

(a) PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Follow protective measures provided in section 2 and section 8.

Contain spill with dike to prevent entry into sewers or waterways. Spills or releases should be reported, if required, to the appropriate local, state and federal agencies.

(b) METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP

Absorb spill using suitable absorbent. Sweep or vacuum absorbent and place in containers for recovery or disposal. Dispose of clean-up materials per section 13.

7. HANDLING AND STORAGE

(a) PRECAUTIONS FOR SAFE HANDLING

Avoid breathing mist or vapor. Use with adequate ventilation. Wear NIOSH/MSHA approved respiratory protection if there is potential for exposure above the exposure limits.

(b) CONDITIONS FOR SAFE STORAGE, INCOMPATIBILITIES

Keep container tightly closed and properly labeled. Store in a cool, dry and locked area.

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

Incompatibilities: See section 10

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

(a) EXPOSURE LIMITS

<i>Component</i>	<i>Weight Percent</i>	<i>OSHA</i>	<i>ACGIH TLV</i>
Bisphenol A Diglycidel Ether Resin	92.3%	Not established	Not established

(b) ENGINEERING CONTROLS

Since this material may be irritating to skin and mucous membranes, general room ventilation plus local exhaust at points of emission should be used to maintain levels of airborne contaminants as low as feasibly possible.

(c) PERSONAL PROTECTION

Respiratory: Wear a NIOSH/MSHA approved respirator following manufacturer's recommendations, where airborne contaminants may occur.

Eye/face: Wear safety glasses with side shields or chemical safety goggles and a face shield as appropriate (ANSI Z87.1).

Skin: Contact should be prevented by use of appropriate personal protective clothing. Wear chemical resistant gloves such as rubber, neoprene or vinyl.

Other: Emergency shower and eyewash facility should be in close proximity (ANSI Z358.1).

9. PHYSICAL AND CHEMICAL PROPERTIES

(a) Appearance and Odor: Royal blue viscous liquid.

(b) Odor Threshold: Not available

(c) pH: Not available

(d) Specific Gravity (H₂O = 1): 1.16

(e) Melting Point/Freezing Point: -15 to 5⁰ C

(f) Boiling Point @ 760 mm Hg/Boiling Point Range: Not available

(g) Flash Point: 490⁰F

(h) Evaporation rate: Not available

(I) Flammability: Not a flammable liquid but will burn under fire conditions.

(j) Lower explosive limit (LEL)/Upper explosive limit (UEL): Not available/ Not available

(k) Vapor Pressure: 0.03 mm Hg at 77⁰C

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

- (l) Vapor density:** Not available
- (m) Relative density:** 1.16g/cm³
- (n) Solubility in Water:** Not available
- (o) Partition coefficient:** Log Pow: 2.8
- (p) Auto ignition temperature:** Not available
- (q) Decomposition temperature:** Decomposition starts at 124⁰ C
- (r) Viscosity:** Not available

10. STABILITY AND REACTIVITY

a) REACTIVITY

No data available

b) CHEMICAL STABILITY

Stable under recommended storage conditions

c) POSSIBILITY OF HAZARDOUS REACTION

No data available

d) CONDITIONS TO AVOID

See 10 a, c and e

e) INCOMPATIBLE MATERIALS

Strong oxidizing agents, acids, amines, bases.

f) HAZARDOUS DECOMPOSITION PRODUCTS

Carbon monoxide & carbon dioxide.

11. TOXICOLOGICAL INFORMATION

a) INFORMATION ON LIKELY ROUTES OF EXPOSURE

See section 4.

b) SYMPTOMS RELATED TO THE PHYSICAL, CHEMICAL AND TOXICOLOGICAL CHARACTERISTICS

See sections 2 and 4.

c) DELAYED AND IMMEDIATE EFFECTS

See section 4.

d) NUMERICAL MEASURES OF TOXICITY

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

ACUTE ORAL TOXICITY: LD50: >13 g/kg (rat)

e) CARCINOGENICITY

This product does not contain any substances at > 0.1 weight % that are considered by OSHA, NTP, IARC or AGCIH to be “probable” or “suspected” carcinogens.

12. ECOLOGICAL INFORMATION

a) ECOTOXICITY

No data available

b) PERSISTANCE AND DEGRADABILITY

No data available

c) BIOACCUMULATIVE POTENTIAL

No data available

d) MOBILITY IN SOIL

No data available

e) OTHER ADVERSE EFFECTS

None known.

13. DISPOSAL CONSIDERATIONS

Dispose of all waste, contaminated containers and contaminated equipment in accordance with all applicable federal, state and local health and environmental regulations. Recovery and reuse, rather than disposal, should be the ultimate goal of handling efforts.

14. TRANSPORTATION INFORMATION

a) UN NUMBER:

Not regulated

b) UN PROPER SHIPPING NAME:

NA

c) TRANSPORT HAZARD CLASSES

NA

d) PACKING GROUP

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

NA

e) ENVIRONMENTAL HAZARDS

NA

e) TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL

None

f) SPECIAL PRECAUTIONS

NA

g) IATA

Not regulated

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees.

To aid our customers in complying with regulatory requirements, SARA Title III Hazard Categories for this product are indicated below. If the word "YES" appears next to any category, this product may be reportable by you under the requirements of 40.CFR.370. Please consult those regulations for details.

SARA/TITLE III HAZARD CATEGORIES:

Immediate (Acute) Health:	YES	Reactive Hazard:	NO
Delayed (Chronic) Health:	YES	Sudden Release of Pressure:	NO
Fire Hazard:	NO		

TSCA: All components contained in this substance are listed on the TSCA inventory.

HMIS HAZARD RATINGS:

HEALTH HAZARD: 3 FIRE HAZARD: 1 REACTIVITY: 0

STATE REGULATIONS: Consult local laws for applicability.

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

INTERNATIONAL REGULATIONS: Consult the regulations of the importing country.

16. OTHER INFORMATION

SDS LEGEND:

ACGIH = American Conference of Governmental Industrial Hygienists

ANSI = American National Standards Institute

CAS = Chemical Abstracts Service Registry Number

CEILING = Ceiling Limit (Duration is for 15 minutes, unless otherwise noted.)

CEL = Corporate Exposure Limit

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

CFR = Code of Federal Regulations (USA)

COC = Cleveland Open Cup

DOT = Department of Transportation

LEL = Lower explosive limit

MARPOL = International Convention for the Prevention of Pollution from Ships

MSHA = Mine Safety and health Administration

NTP = National Toxicological Program

NIOSH = National Institute for Occupational Safety and Health

OSHA = Occupational Safety and Health Administration

GHS = Global Harmonized System

IARC = International Agency for Research on Cancer

PEL = Permissible Exposure Limit (OSHA)

PPM = parts per million

RQ = Reportable Quantity per 40 CFR 355

SARA = Superfund Amendments and Re-authorization Act

SDS = Safety Data Sheet

STEL = Short Term Exposure Limit (Duration is for 15 minutes, unless otherwise noted.)

TLV = Threshold Limit Value (ACGIH)

TWA = Time Weighted Average (8 hr)

UEL = Upper Explosive Limit

* = See section 3 Hazards Identification - Repeated Exposure (Chronic)

PRODUCT NAME: No. 1 Vary Flex Epoxy Resin

IMPORTANT: The information presented herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge. **NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR PURPOSE, OR OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, STABILITY OR OTHERWISE.**

This information is not intended to be all-inclusive as to the manner and conditions of use, handling and storage. Other factors may involve other or additional safety or performance considerations. While our technical personnel will be happy to respond to questions regarding safe handling and use procedures, safe handling and use remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as a recommendation to infringe any existing patents or violate any Federal, State or local laws, rules, regulations or ordinances.

MOST RECENT VERSION OF THIS SDS: 03/09/21